



سلكوپلاست للكابلات (ش.م.م.)
SELCOPLAST CABLES CO. (S.A.E)

PRODUCT DATA SHEET

Cable Description

Cable Size : 240 mm² (Bare)
Standard Specification Applied To Cable : IEC 60228
Rated Voltage :
Cable Description : Stranded Copper Conductor (CU)

Conductor

Standard Specification Applied To Conductor : IEC 60228
NO. Of Cores per Cable : 1
Nominal Cross- Sectional Area Per core : 240 mm²
Nominal Number Of Strands Per core : 61
Diameter Of Each Strand : 2.25 mm
Material Of Core : Copper
Type : Class-2
Cross- Sectional Area Of Each Strand : 3.974 mm²
Overall Diameter Of Conductor : 20.25 mm
D.C. Resistance Of Conductor At 20°C Per Km (max.) : 0.0754 Ω/km

Cable Dimension (Nominal) :

Approx. Overall Diameter : 20.25 mm

Company : SELCOPLAST CABLES
Q.C. Department



ISO 9001:2008



OHSAS 18001:2007



السلامة الأوروبية



التوحيد القياسي

حاصلون على:

المصانع

مدينة العاشر من رمضان

تليفون: ٠١٥/٣٦١٨٢٢ - ٠١٥/٣٦١٨٢٣ - فاكس: ٠١٥/٣٦٥٠٨٠

المخازن والمبيعات

١ شارع إدريس - الشرايية

تليفون: ٢٢٣٥٦٩١٧ - ٢٢٣٥٥٤١٦ - فاكس: ٢٢٣٣٨١٣٧