



سلكوبلاست للكابلات (ش.م.م.)
SELCOPLAST CABLES CO. (S.A.E)

PRODUCT DATA SHEET

Cable Description

Cable Size : 1.5 mm²
Standard Specification Applied To Cable : DIN ISO 6722 - IEC 60228
Cable Code : Automotive Cable (FLY 1.5)
Cable Description : Flexible Copper Conductor Insulated With Polyvinyl Chloride (CU / PVC)

Conductor

Standard Specification Applied To Conductor : IEC 60228
NO. Of Cores per Cable : 1
Nominal Cross- Sectional Area Per core : 1.5 mm²
Nominal Number Of Strands Per core : 30
Diameter Of Each Strand : 0.25 mm
Material Of Core : Copper
Type : Class-5
Cross- Sectional Area Of Each Strand : 0.049 mm²
Overall Diameter Of Conductor : 1.7 mm
D.C. Resistance Of Conductor At 20c Per Km (max.) : 12.7 Ω/km

Insulation

Material Of Insulation : Polyvinyl Chloride105c
Colour Per Core :
Nominal Thickness Of Insulation : 0.60 mm
Approx. Overall Cable Diameter : 3.0 mm

Company : SELCOPLAST CABLES
Q.C. Depatment



ISO 9001:2008



OHSAS 18001:2007



السلامة الأوروبية



التوحيد القياسي

حاصلون على:

المصانع

مدينة العاشر من رمضان

تليفون: ٠١٥/٣٦١٨٢٢ - ٠١٥/٣٦١٨٢٣ - فاكس: ٠١٥/٣٦٥٠٨٠

المخازن والمبيعات

١ شارع إدريس - الشرايية

تليفون: ٢٢٣٥٦٩١٧ - ٢٢٣٥٥٤١٦ - فاكس: ٢٢٣٣٨١٣٧