



سلكو بلاست للكابلات (ش.م.م.)
SELCOPLAST CABLES CO. (S.A.E)

PRODUCT DATA SHEET

Cable Description

Cable Size : 20.0 mm²
Standard Specification Applied To Cable : DIN ISO 6722 - IEC 60228
Cable Code : Automotive Cable (FLY 20.0)
Cable Description : Flexible Copper Conductor Insulated With Polyvinyl Chloride (CU / PVC)

Conductor

Standard Specification Applied To Conductor : IEC 60228
NO. Of Cores per Cable : 1
Nominal Cross- Sectional Area Per core : 20 mm²
Nominal Number Of Strands Per core : 280
Diameter Of Each Strand : 0.30 mm
Material Of Core : Copper
Type : Class-5
Cross- Sectional Area Of Each Strand : 0.07065 mm²
Overall Diameter Of Conductor : 6.9 mm
D.C. Resistance Of Conductor At 20c Per Km (max.) : 0.955 Ω/km

Insulation

Material Of Insulation : Polyvinyl Chloride 105c
Colour Per Core :
Nominal Thickness Of Insulation : 1.10 mm
Approx. Overall Cable Diameter : 9.1 mm

Company : SELCOPLAST CABLES
Q.C. Depatment



ISO 9001:2008



OHSAS 18001:2007



السلامة الأوروبية



التوحيد القياسي

حاصلون على:

المصانع

مدينة العاشر من رمضان

تليفون: ٠١٥/٣٦١٨٢٢ - ٠١٥/٣٦١٨٢٣ - فاكس: ٠١٥/٣٦٥٠٨٠

المخازن والمبيعات

١ شارع إدريس - الشرايية

تليفون: ٢٢٣٥٦٩١٧ - ٢٢٣٥٥٤١٦ - فاكس: ٢٢٣٣٨١٣٧