



سلكوبلاست للكابلات (ش.م.م.)
SELCOPLAST CABLES CO. (S.A.E)

PRODUCT DATA SHEET

Cable Description

Cable Size : 0.75 mm²
Standard Specification Applied To Cable : DIN ISO 6722 - IEC 60228
Cable Code : Automotive Cable (FLYR 0.75)
Cable Description : Flexible Copper Conductor Insulated With Thin Wall Polyvinyl Chloride (CU / PVC)

Conductor

Standard Specification Applied To Conductor : IEC 60228
NO. Of Cores per Cable : 1
Nominal Cross- Sectional Area Per core : 0.75 mm²
Nominal Number Of Strands Per core : 24
Diameter Of Each Strand : 0.20 mm
Material Of Core : Copper
Type : Class-5
Cross- Sectional Area Of Each Strand : 0.0314 mm²
Overall Diameter Of Conductor : 1.2 mm
D.C. Resistance Of Conductor At 20c Per Km (max.) : 24.7 Ω/km

Insulation

Material Of Insulation : Polyvinyl Chloride105c
Colour Per Core :
Nominal Thickness Of Insulation : 0.24 mm
Approx. Overall Cable Diameter : 1.9 mm

Company : SELCOPLAST CABLES
Q.C. Depatment

حاصلون على:



ISO 9001:2008



OHSAS 18001:2007



السلامة الأوروبية



التوحيد القياسي

المصانع

مدينة العاشر من رمضان

تليفون: ٠١٥/٣٦١٨٢٢ - ٠١٥/٣٦١٨٢٣ - فاكس: ٠١٥/٣٦٥٠٨٠

المخازن والمبيعات

١ شارع إدريس - الشرايية

تليفون: ٢٢٣٥٦٩١٧ - ٢٢٣٥٥٤١٦ - فاكس: ٢٢٣٣٨١٣٧