



سلكوبلاست للكابلات (ش.م.م.)  
SELCOPLAST CABLES CO. (S.A.E)

## PRODUCT DATA SHEET

### Cable Description

Cable Size : 4.0 mm<sup>2</sup>  
Standard Specification Applied To Cable : DIN ISO 6722 - IEC 60228  
Cable Code : Automotive Cable (FLRY 4.0)  
Cable Description : Flexible Copper Conductor Insulated With Thin Wall Polyvinyl Chloride (CU / PVC)

### Conductor

Standard Specification Applied To Conductor : IEC 60228  
NO. Of Cores per Cable : 1  
Nominal Cross- Sectional Area Per core : 4.0 mm<sup>2</sup>  
Nominal Number Of Strands Per core : 56  
Diameter Of Each Strand : 0.30 mm  
Material Of Core : Copper  
Type : Class-5  
Cross- Sectional Area Of Each Strand : 0.07065 mm<sup>2</sup>  
Overall Diameter Of Conductor : 2.75 mm  
D.C. Resistance Of Conductor At 20c Per Km (max.) : 4.71 Ω/km

### Insulation

Material Of Insulation : Polyvinyl Chloride105c  
Colour Per Core : .....  
Nominal Thickness Of Insulation : 0.32 mm  
Approx. Overall Cable Diameter : 3.7 mm

Company : SELCOPLAST CABLES  
Q.C. Depatment



ISO 9001:2008



OHSAS 18001:2007



السلامة الأوروبية



التوحيد القياسي

حاصلون على:

المصانع

مدينة العاشر من رمضان

تليفون: ٠١٥/٣٦١٨٢٢ - ٠١٥/٣٦١٨٢٣ - فاكس: ٠١٥/٣٦٥٠٨٠

المخازن والمبيعات

١ شارع إدريس - الشرايية

تليفون: ٢٢٣٥٦٩١٧ - ٢٢٣٥٥٤١٦ - فاكس: ٢٢٣٣٨١٣٧