سلكوبلاست للكابلات (ش.م.م.)
SELCOPLAST CABLES CO. (S.A.E)

# PRODUCT DATA SHEET

## Cable Description

| | | |
|---|---|---|
| ***Cable Size*** | : | *1.5 mm²* |
| ***Standard Specification Applied To Cable*** | : | *DIN ISO 6722 - IEC 60228* |
| ***Cable Code*** | : | *Automotive Cable ( FLY 1.5 )* |
| ***Cable Description*** | : | *Flexible Copper Conductor Insulated With Polyvinyl Chloride (CU / PVC)* |

## Conductor

| | |
|---|---|
| ***Standard Specification Applied To Conductor*** : | *IEC 60228* |
| ***NO. Of Cores per Cable*** : | *1* |
| ***Nominal Cross- Sectional Area Per core*** : | *1.5 mm²* |
| ***Nominal Number Of Strands Per core*** : | *30* |
| ***Diameter Of Each Strand*** : | *0.25 mm* |
| ***Material Of Core*** : | *Copper* |
| ***Type*** : | *Class-5* |
| ***Cross- Sectional Area Of Each Strand*** : | *0.049 mm²* |
| ***Overall Diameter Of Conductor*** : | *1.7 mm* |
| ***D.C. Resistance Of Conductor At 20ċ Per Km (max.)*** : | *12.7 Ω/km* |

## Insulation

| | | |
|---|---|---|
| ***Material Of Insulation*** : | *Polyvinyl Chloride105ċ* | |
| ***Colour Per Core*** : | ..... | |
| ***Nominal Thickness Of Insulation*** | : | *0.60 mm* |
| ***Approx. Overall Cable Diameter*** | : | *3.0 mm* |

***Company :*** ***SELCOPLAST CABLES***

***Q.C. Depatment***




المصانع
مدينة العاشر من رمضان
تليفون: ٠١٥/٣٦١٨٢٢ - ٠١٥/٣٦١٨٢٣ - فاكس: ٠١٥/٣٦٥٠٨٠
المخازن والمبيعات
١ شارع إدريس - الشرابية
تليفون: ٢٢٣٥٦٩١٧ - ٢٢٣٥٥٤١٦ - فاكس: ٢٢٣٣٨١٣٧