سلكوبلاست للكابلات (ش.م.م.)
SELCOPLAST CABLES CO. (S.A.E)

PRODUCT DATA SHEET

Cable Description

Cable Size	:	*40 mm²*
Standard Specification Applied To Cable	:	*DIN ISO 6722 - IEC 60228*
Cable Code	:	*Automotive Cable (FLY 40.0)*
Cable Description	:	*Flexible Copper Conductor Insulated With Polyvinyl Chloride (CU / PVC)*

Conductor

Standard Specification Applied To Conductor :	*IEC 60228*
NO. Of Cores per Cable :	*1*
Nominal Cross- Sectional Area Per core :	*40 mm²*
Nominal Number Of Strands Per core :	*560*
Diameter Of Each Strand :	*0.30 mm*
Material Of Core :	*Copper*
Type :	*Class-5*
Cross- Sectional Area Of Each Strand :	*0.07065 mm²*
Overall Diameter Of Conductor :	*9.6 mm*
D.C. Resistance Of Conductor At 20ċ Per Km (max.) :	0.473 Ω/km

Insulation

Material Of Insulation	:	*Polyvinyl Chloride105ċ*
Colour Per Core	:	.....
Nominal Thickness Of Insulation	:	*1.40 mm*
Approx. Overall Cable Diameter	:	*12.4 mm*

Company : *SELCOPLAST CABLES*

Q.C. Depatment

المصانع
مدينة العاشر من رمضان
تليفون: ٠١٥/٣٦١٨٢٢ - ٠١٥/٣٦١٨٢٣ - فاكس: ٠١٥/٣٦٥٠٨٠

المخازن والمبيعات
١ شارع إدريس - الشرابية
تليفون: ٢٢٣٥٦٩١٧ - ٢٢٣٥٥٤١٦ - فاكس: ٢٢٣٣٨١٣٧

حاصلون على:

ISO 9001:2008 | OHSAS 18001:2007 | السلامة الأوروبية | التوحيد القياسى