



سلكوبلاست للكابلات (ش.م.م.)  
SELCOPLAST CABLES CO. (S.A.E)

## PRODUCT DATA SHEET

### Cable Description

Cable Size : 4X2.5 mm<sup>2</sup>  
Standard Specification Applied To Cable : IEC 60502 - IEC 60228  
Rated Voltage : 600 / 1000 Volt  
Cable Description : Flexible Copper Conductor Insulated With X.L.P.E. And Sheathed With Polyvinyl Chloride(CU / XLPE / PVC)

### Conductor

Standard Specification Applied To Conductor : IEC 60228  
NO. Of Cores per Cable : 4  
Nominal Cross- Sectional Area Per core : 2.5 mm<sup>2</sup>  
Nominal Number Of Strands Per core : 50  
Diameter Of Each Strand : 0.25 mm  
Material Of Core : Copper  
Type : Class-5  
Cross- Sectional Area Of Each Strand : 0.04906 mm<sup>2</sup>  
Overall Diameter Of Conductor : 2.01 mm  
D.C. Resistance Of Conductor At 20°c Per Km (max.) : 7.98 Ω/km

### Insulation

Material Of Insulation : X.L.P.E.  
Colour Per Core : Red – Yellow – Blue – Black  
Nominal Thickness Of Insulation Per Core : 0.70 mm  
Min. Insulation Resistance Per Core Per Km Length Of Cable At 70°c : 0.009 M ohm.Km  
Test Voltage Between Cores And Earth ( AC KV . Time min ) : 3000V for 5 min  
Heat Resistance Test ( Temperature °c . Time min ) : 150 °c for 1 hour

حاصلون على:



ISO 9001:2008



OHSAS 18001:2007



السلامة الأوروبية



التوحيد القياسي

المصانع

مدينة العاشر من رمضان

تليفون: ٠١٥/٣٦١٨٢٢ - ٠١٥/٣٦١٨٢٣ - فاكس: ٠١٥/٣٦٥٠٨٠

المخازن والمبيعات

١ شارع إدريس - الشرايية

تليفون: ٢٢٣٥٦٩١٧ - ٢٢٣٥٥٤١٦ - فاكس: ٢٢٣٣٨١٣٧



سلكوپلاست للكابلات (ش.م.م.)  
SELCOPLAST CABLES CO. (S.A.E)

## PRODUCT DATA SHEET

### Over Sheath

Material Of Outer Jacket : Polyvinyl Chloride  
Thickness Of Outer Jacket : 1.80 mm  
Colour Of Outer Jacket : Gray Or Black

### Cable Dimension ( Nominal ) :

Approx. External Cable Diameter : 12.20 mm

Company : SELCOPLAST CABLES  
Q.C. Department



ISO 9001:2008



OHSAS 18001:2007



السلامة الأوروبية



التوحيد القياسي

حاصلون على:

المصانع

مدينة العاشر من رمضان

تليفون: ٠١٥/٣٦١٨٢٢ - ٠١٥/٣٦١٨٢٣ - فاكس: ٠١٥/٣٦٥٠٨٠

المخازن والمبيعات

١ شارع إدريس - الشرايية

تليفون: ٢٢٣٥٦٩١٧ - ٢٢٣٥٥٤١٦ - فاكس: ٢٢٣٣٨١٣٧