سلكوبلاست للكابلات (ش.م.م.)
SELCOPLAST CABLES CO. (S.A.E)

# PRODUCT DATA SHEET

## Cable Description

| | | |
|---|---|---|
| ***Cable Size*** | : | *2X16 mm²* |
| ***Standard Specification Applied To Cable*** | : | *IEC 60227 - IEC 60228* |
| ***Rated Voltage*** | : | *300 / 500 Volt* |
| ***Cable Description*** | : | *Flexible Copper Conductor Insulated With Polyvinyl Chloride And Sheathed With Polyvinyl Chloride(CU / PVC / PVC)* |

## Conductor

| | |
|---|---|
| ***Standard Specification Applied To Conductor :*** | *IEC 60228* |
| ***NO. Of Cores per Cable :*** | *2* |
| ***Nominal Cross- Sectional Area Per core :*** | *16 mm²* |
| ***Nominal Number Of Strands Per core :*** | *224* |
| ***Diameter Of Each Strand :*** | *0.30 mm* |
| ***Material Of Core :*** | *Copper* |
| ***Type :*** | *Class-5* |
| ***Cross- Sectional Area Of Each Strand :*** | *0.07065 mm²* |
| ***Overall Diameter Of Conductor :*** | *5.2 mm* |
| ***D.C. Resistance Of Conductor At 20ċ Per Km (max.) :*** | *1.21 Ω/km* |

## Insulation

***Material Of Insulation :*** *Polyvinyl Chloride*

***Colour Per Core :*** *Red – Black*

***Nominal Thickness Of Insulation Per Core :*** *1.00 mm*

***Min. Insulation Resistance Per Core Per Km Length Of Cable At 70ċ :*** *0.0046 M ohm.Km*

***Test Voltage Between Cores And Earth ( AC KV . Time min ) :*** *2000V for 5 min*

***Heat Resistance Test ( Temperature ċ . Time min ) :*** *150 ċ for 1 hour*

سلكوبلاست للكابلات (ش.م.م.)
SELCOPLAST CABLES CO. (S.A.E)

# PRODUCT DATA SHEET

## Over Sheath

| | | |
|---|---|---|
| ***Material Of Outer Jacket*** | : | *Polyvinyl Chloride* |
| ***Thickness Of Outer Jacket*** | : | *1.4 mm* |
| ***Colour Of Outer Jacket*** | : | *White , Gray , Or Black* |

## Cable Dimension ( Nominal ) :

| | | |
|---|---|---|
| ***Nominal External Cable Diameter*** | : | *15.5 : 20.0 mm* |

***Company :*** ***SELCOPLAST CABLES***

***Q.C. Depatment***