سلكوبلاست للكابلات (ش.م.م.)
SELCOPLAST CABLES CO. (S.A.E)

# PRODUCT DATA SHEET

## Cable Description

| | | |
|---|---|---|
| *Cable Size* | : | *4X95 mm²* |
| *Standard Specification Applied To Cable* | : | *IEC 60502 - IEC 60228* |
| *Rated Voltage* | : | *600 / 1000 Volt* |
| *Cable Description* | : | *Stranded Copper Conductor Insulated With Cross-Linked Polyethylene And Sheathed With Polyvinyl Chloride(CU / XLPE / PVC)* |

## Conductor

| | |
|---|---|
| *Standard Specification Applied To Conductor :* | *IEC 60228* |
| *NO. Of Cores per Cable :* | *4* |
| *Nominal Cross- Sectional Area Per core :* | *95 mm²* |
| *Nominal Number Of Strands Per core :* | *19* |
| *Diameter Of Each Strand :* | *2.50 mm* |
| *Material Of Core :* | *Copper* |
| *Type :* | *Class-2* |
| *Cross- Sectional Area Of Each Strand :* | *4.906 mm²* |
| *Overall Diameter Of Conductor :* | *12.5 mm* |
| *D.C. Resistance Of Conductor At 20ċ Per Km (max.) :* | 0.193 Ω/km |

## Insulation

*Material Of Insulation : Cross-Linked Polyethylene(XLPE)*

*Colour Per Core : Red – Yellow – Blue – Black*

*Nominal Thickness Of Insulation Per Core : 1.10 mm*

*Min. Insulation Resistance Per Core Per Km Length Of Cable At 90ċ : 0.0035 M ohm.Km*

*Test Voltage Between Cores And Earth ( AC KV . Time min ) : 3000V for 5 min*

*Heat Resistance Test ( Temperature ċ . Time min ) : 150 ċ for 1 hour*


حاصلون على:
ISO 9001:2008 OHSAS 18001:2007 السلامة الأوروبية التوحيد القياسى

المصانع
مدينة العاشر من رمضان
تليفون: ٠١٥/٣٦١٨٢٢ - ٠١٥/٣٦١٨٢٣ - فاكس: ٠١٥/٣٦٥٠٨٠
المخازن والمبيعات
١ شارع إدريس - الشرابية
تليفون: ٢٢٣٥٦٩١٧ - ٢٢٣٥٥٤١٦ - فاكس: ٢٢٣٣٨١٣٧

سلكوبلاست للكابلات (ش.م.م.)
SELCOPLAST CABLES CO. (S.A.E)

# PRODUCT DATA SHEET

## Over Sheath

| | | |
|---|---|---|
| *Material Of Outer Jacket* | : | *Polyvinyl Chloride* |
| *Thickness Of Outer Jacket* | : | *2.20 mm* |
| *Colour Of Outer Jacket* | : | *Gray Or Black* |

## Cable Dimension ( Nominal ) :

| | | |
|---|---|---|
| *Approx. External Cable Diameter* | : | *39.90 mm* |

*Company :* *SELCOPLAST CABLES*

*Q.C. Depatment*


المصانع
مدينة العاشر من رمضان
تليفون: ٠١٥/٣٦١٨٢٢ - ٠١٥/٣٦١٨٢٣ - فاكس: ٠١٥/٣٦٥٠٨٠

المخازن والمبيعات
١ شارع إدريس - الشرابية
تليفون: ٢٢٣٥٦٩١٧ - ٢٢٣٥٥٤١٦ - فاكس: ٢٢٣٣٨١٣٧



حاصلون على:
التوحيد القياسى
السلامة الأوروبية
OHSAS 18001:2007
ISO 9001:2008