سلكوبلاست للكابلات (ش.م.م.)
SELCOPLAST CABLES CO. (S.A.E)

PRODUCT DATA SHEET

Cable Description

Cable Size	:	4X25 mm^2
Standard Specification Applied To Cable	:	IEC 60227 - IEC 60228
Rated Voltage	:	300 / 500 Volt
Cable Description	:	Stranded Copper Conductor Insulated With Polyvinyl Chloride And Sheathed With Polyvinyl Chloride(CU / PVC / PVC)

Conductor

Standard Specification Applied To Conductor :	IEC 60228
NO. Of Cores per Cable :	4
Nominal Cross- Sectional Area Per core :	25.0 mm^2
Nominal Number Of Strands Per core :	19
Diameter Of Each Strand :	1.30 mm
Material Of Core :	Copper
Type :	Class-2
Cross- Sectional Area Of Each Strand :	1.3266 mm^2
Overall Diameter Of Conductor :	6.5 mm
D.C. Resistance Of Conductor At 20ċ Per Km (max.) :	0.727 Ω/km

Insulation

Material Of Insulation : Polyvinyl Chloride

Colour Per Core : Red – Yellow – Blue - Black

Nominal Thickness Of Insulation Per Core : 1.20 mm

Min. Insulation Resistance Per Core Per Km Length Of Cable At 70ċ : 0.005 M ohm.Km

Test Voltage Between Cores And Earth (AC KV . Time min) : 2000V for 5 min

Heat Resistance Test (Temperature ċ . Time min) : 150 ċ for 1 hour

حاصلون على:
ISO 9001:2008 OHSAS 18001:2007 السلامة الأوروبية التوحيد القياسى

المصانع
مدينة العاشر من رمضان
تليفون: ٠١٥/٣٦١٨٢٢ - ٠١٥/٣٦١٨٢٣ - فاكس: ٠١٥/٣٦٥٠٨٠

المخازن والمبيعات
١ شارع إدريس - الشرابية
تليفون: ٢٢٣٥٦٩١٧ - ٢٢٣٥٥٤١٦ - فاكس: ٢٢٣٣٨١٣٧

سلكوبلاست للكابلات (ش.م.م.)
SELCOPLAST CABLES CO. (S.A.E)

PRODUCT DATA SHEET

Over Sheath

Material Of Outer Jacket	:	*Polyvinyl Chloride*
Thickness Of Outer Jacket	:	*1.6 mm*
Colour Of Outer Jacket	:	*Gray , Or Black*

Cable Dimension (Nominal) :

Nominal External Cable Diameter	:	*22.5 : 28.5 mm*

Company : ***SELCOPLAST CABLES***

Q.C. Depatment