سلكوبلاست للكابلات (ش.م.م.)
SELCOPLAST CABLES CO. (S.A.E)

PRODUCT DATA SHEET

Cable Description

Cable Size	:	*3X1.0 mm²*
Standard Specification Applied To Cable	:	*IEC 60245 - IEC 60228*
Rated Voltage	:	*300 / 500 Volt*
Cable Description	:	*Flexible Copper Conductor Insulated With Rubber And Sheathed With Rubber (CU / RU / RU)*

Conductor

Standard Specification Applied To Conductor :	*IEC 60228*
NO. Of Cores per Cable :	*3*
Nominal Cross- Sectional Area Per core :	*1.0 mm²*
Nominal Number Of Strands Per core :	*32*
Diameter Of Each Strand :	*0.20 mm*
Material Of Core :	*Copper*
Type :	*Class-5*
Cross- Sectional Area Of Each Strand :	*0.0314 mm²*
Overall Diameter Of Conductor :	*1.3 mm*
D.C. Resistance Of Conductor At 20ċ Per Km (max.) :	19.5 Ω/km

Insulation

Material Of Insulation : *Rubber*

Colour Per Core : *Red – Yellow - Blue*

Nominal Thickness Of Insulation Per Core : *0.60 mm*

Min. Insulation Resistance Per Core Per Km Length Of Cable At 90ċ : *0.013 M ohm.Km*

Test Voltage Between Cores And Earth (AC KV . Time min) : *2000V for 5 min*

Heat Resistance Test (Temperature ċ . Time min) : *150 ċ for 1 hour*

سلكوبلاست للكابلات (ش.م.م.)
SELCOPLAST CABLES CO. (S.A.E)

PRODUCT DATA SHEET

Over Sheath

Material Of Outer Jacket	:	*Rubber*
Thickness Of Outer Jacket	:	*0.90 mm*
Colour Of Outer Jacket	:	.....

Cable Dimension (Nominal) :

Approx. External Cable Diameter	:	*6.5 : 8.5 mm*

Company : SELCOPLAST CABLES

Q.C. Depatment