سلكوبلاست للكابلات (ش.م.م.)
SELCOPLAST CABLES CO. (S.A.E)

# PRODUCT DATA SHEET

## Cable Description

| | | |
|---|---|---|
| *Cable Size* | : | *95 mm²* |
| *Standard Specification Applied To Cable* | : | *IEC 60245 - IEC 60228* |
| *Rated Voltage* | : | *450 / 750 Volt* |
| *Cable Description* | : | *Flexible Copper Conductor Insulated With Rubber (CU / RU)* |

## Conductor

| | |
|---|---|
| *Standard Specification Applied To Conductor :* | *IEC 60228* |
| *NO. Of Cores per Cable :* | *1* |
| *Nominal Cross- Sectional Area Per core :* | *95 mm²* |
| *Nominal Number Of Strands Per core :* | *1330* |
| *Diameter Of Each Strand :* | *0.30 mm* |
| *Material Of Core :* | *Copper* |
| *Type :* | *Class-5* |
| *Cross- Sectional Area Of Each Strand :* | *0.07065 mm²* |
| *Overall Diameter Of Conductor :* | *14.7 mm* |
| *D.C. Resistance Of Conductor At 20ċ Per Km (max.) :* | 0.206 Ω/km |

## Insulation

*Material Of Insulation : Rubber*

*Colour Per Core : .....*

*Nominal Thickness Of Insulation Per Core : 1.80 mm*

*Min. Insulation Resistance Per Core Per Km Length Of Cable At 90ċ : 0.004 M ohm.Km*

*Test Voltage Between Cores And Earth ( AC KV . Time min ) : 2500V for 5 min*

*Heat Resistance Test ( Temperature ċ . Time min ) : 150 ċ for 1 hour*




المصانع
مدينة العاشر من رمضان
تليفون: ٠١٥/٣٦١٨٢٢ - ٠١٥/٣٦١٨٢٣ - فاكس: ٠١٥/٣٦٥٠٨٠
المخازن والمبيعات
١ شارع إدريس - الشرابية
تليفون: ٢٢٣٥٦٩١٧ - ٢٢٣٥٥٤١٦ - فاكس: ٢٢٣٣٨١٣٧

سلكوبلاست للكابلات (ش.م.م.)
SELCOPLAST CABLES CO. (S.A.E)

# PRODUCT DATA SHEET

## Over Sheath

| | | |
|---|---|---|
| *Material Of Outer Jacket* | : | ..... |
| *Thickness Of Outer Jacket* | : | ..... |
| *Colour Of Outer Jacket* | : | ..... |

## Cable Dimension ( Nominal ) :

| | | |
|---|---|---|
| *Approx. External Cable Diameter* | : | *15.5 : 19.3 mm* |

*Company : SELCOPLAST CABLES*

*Q.C. Depatment*


المصانع
مدينة العاشر من رمضان
تليفون: ٠١٥/٣٦١٨٢٢ - ٠١٥/٣٦١٨٢٣ - فاكس: ٠١٥/٣٦٥٠٨٠

المخازن والمبيعات
١ شارع إدريس - الشرابية
تليفون: ٢٢٣٥٦٩١٧ - ٢٢٣٥٥٤١٦ - فاكس: ٢٢٣٣٨١٣٧



حاصلون على:
التوحيد القياسى
السلامة الأوروبية
OHSAS 18001:2007
ISO 9001:2008