سلكوبلاست للكابلات (ش.م.م.)
SELCOPLAST CABLES CO. (S.A.E)

PRODUCT DATA SHEET

Cable Description

Cable Size	**:**	*0.5 mm²*
Standard Specification Applied To Cable	**:**	*IEC 60227 - IEC 60228*
Rated Voltage	**:**	*300 / 500 Volt*
Cable Description	**:**	*Flexible Copper Conductor Insulated With Polyvinyl Chloride (CU / PVC)*

Conductor

Standard Specification Applied To Conductor :	*IEC 60228*
NO. Of Cores per Cable :	*1*
Nominal Cross- Sectional Area Per core :	*0.5 mm²*
Nominal Number Of Strands Per core :	*16*
Diameter Of Each Strand :	*0.20 mm*
Material Of Core :	*Copper*
Type :	*Class-5*
Cross- Sectional Area Of Each Strand :	*0.0314 mm²*
Overall Diameter Of Conductor :	*0.9 mm*
D.C. Resistance Of Conductor At 20ċ Per Km (max.) :	*39.0 Ω/km*

Insulation

Material Of Insulation : *Polyvinyl Chloride*

Colour Per Core : ……

Nominal Thickness Of Insulation Per Core : *0.60 mm*

Min. Insulation Resistance Per Core Per Km Length Of Cable At 70ċ : *0.013 M ohm.Km*

Test Voltage Between Cores And Earth (AC KV . Time min) : *2000V for 5 min*

Heat Resistance Test (Temperature ċ . Time min) : *150 ċ for 1 hour*

المصانع
مدينة العاشر من رمضان
تليفون: ٠١٥/٣٦١٨٢٢ - ٠١٥/٣٦١٨٢٣ - فاكس: ٠١٥/٣٦٥٠٨٠

المخازن والمبيعات
١ شارع إدريس - الشرابية
تليفون: ٢٢٣٥٦٩١٧ - ٢٢٣٥٥٤١٦ - فاكس: ٢٢٣٣٨١٣٧

حاصلون على:

ISO 9001:2008 | OHSAS 18001:2007 | السلامة الأوروبية | التوحيد القياسى

سلكوبلاست للكابلات (ش.م.م.)
SELCOPLAST CABLES CO. (S.A.E)

PRODUCT DATA SHEET

Over Sheath

Material Of Outer Jacket	:	…….
Thickness Of Outer Jacket	:	…….
Colour Of Outer Jacket	:	…….

Cable Dimension (Nominal) :

Nominal External Cable Diameter	:	≤2.6 *mm*

Company : *SELCOPLAST CABLES*

Q.C. Depatment

المصانع
مدينة العاشر من رمضان
تليفون: ٠١٥/٣٦١٨٢٢ - ٠١٥/٣٦١٨٢٣ - فاكس: ٠١٥/٣٦٥٠٨٠
المخازن والمبيعات
١ شارع إدريس - الشرابية
تليفون: ٢٢٣٥٦٩١٧ - ٢٢٣٥٥٤١٦ - فاكس: ٢٢٣٣٨١٣٧