سلكوبلاست للكابلات (ش.م.م.)
SELCOPLAST CABLES CO. (S.A.E)

PRODUCT DATA SHEET

Cable Description

Cable Size	:	*16 mm²*
Standard Specification Applied To Cable	:	*IEC 60227 - IEC 60228*
Rated Voltage	:	*450 / 750 Volt*
Cable Description	:	*Flexible Copper Conductor Insulated With Polyvinyl Chloride (CU / PVC)*

Conductor

Standard Specification Applied To Conductor :	*IEC 60228*
NO. Of Cores per Cable :	*1*
Nominal Cross- Sectional Area Per core :	*16.0 mm²*
Nominal Number Of Strands Per core :	*224*
Diameter Of Each Strand :	*0.30 mm*
Material Of Core :	*Copper*
Type :	*Class-5*
Cross- Sectional Area Of Each Strand :	*0.07065 mm²*
Overall Diameter Of Conductor :	*5.20 mm*
D.C. Resistance Of Conductor At 20ċ Per Km (max.) :	*1.21 Ω/km*

Insulation

Material Of Insulation : Polyvinyl Chloride

Colour Per Core : .....

Nominal Thickness Of Insulation Per Core : 1.00 mm

Min. Insulation Resistance Per Core Per Km Length Of Cable At 70ċ : 0.0046 M ohm.Km

Test Voltage Between Cores And Earth (AC KV . Time min) : 2500V for 5 min

Heat Resistance Test (Temperature ċ . Time min) : 150 ċ for 1 hour

المصانع
مدينة العاشر من رمضان
تليفون: ٠١٥/٣٦١٨٢٢ - ٠١٥/٣٦١٨٢٣ - فاكس: ٠١٥/٣٦٥٠٨٠

المخازن والمبيعات
١ شارع إدريس - الشرابية
تليفون: ٢٢٣٥٦٩١٧ - ٢٢٣٥٥٤١٦ - فاكس: ٢٢٣٣٨١٣٧

حاصلون على:
ISO 9001:2008 OHSAS 18001:2007 السلامة الأوروبية التوحيد القياسى

سلكوبلاست للكابلات (ش.م.م.)
SELCOPLAST CABLES CO. (S.A.E)

PRODUCT DATA SHEET

Over Sheath

Material Of Outer Jacket	:	…….
Thickness Of Outer Jacket	:	…….
Colour Of Outer Jacket	:	…….

Cable Dimension (Nominal) :

Nominal External Cable Diameter	:	*6.7 : 8.1 mm*

Company : SELCOPLAST CABLES

Q.C. Depatment

المصانع
مدينة العاشر من رمضان
تليفون: ٠١٥/٣٦١٨٢٢ - ٠١٥/٣٦١٨٢٣ - فاكس: ٠١٥/٣٦٥٠٨٠

المخازن والمبيعات
١ شارع إدريس - الشرابية
تليفون: ٢٢٣٥٦٩١٧ - ٢٢٣٥٥٤١٦ - فاكس: ٢٢٣٣٨١٣٧

حاصلون على:
التوحيد القياسى
السلامة الأوروبية
OHSAS 18001:2007
ISO 9001:2008