



سلكو بلاست للكابلات (ش.م.م.)
SELCOPLAST CABLES CO. (S.A.E)

PRODUCT DATA SHEET

Cable Description

Cable Size : 300 mm²
Standard Specification Applied To Cable : IEC 60227 - IEC 60228
Rated Voltage : 450 / 750 Volt
Cable Description : Stranded Copper Conductor Insulated With Polyvinyl Chloride (CU / PVC)

Conductor

Standard Specification Applied To Conductor : IEC 60228
NO. Of Cores per Cable : 1
Nominal Cross- Sectional Area Per core : 300 mm²
Nominal Number Of Strands Per core : 61
Diameter Of Each Strand : 2.50 mm
Material Of Core : Copper
Type : Class-2
Cross- Sectional Area Of Each Strand : 4.906 mm²
Overall Diameter Of Conductor : 22.5 mm
D.C. Resistance Of Conductor At 20°c Per Km (max.) : 0.0601 Ω/km

Insulation

Material Of Insulation : Polyvinyl Chloride
Colour Per Core :
Nominal Thickness Of Insulation Per Core : 2.40 mm
Min. Insulation Resistance Per Core Per Km Length Of Cable At 70°c : 0.0030 M ohm.Km
Test Voltage Between Cores And Earth (AC KV . Time min) : 2500V for 5 min
Heat Resistance Test (Temperature °c . Time min) : 150 °c for 1 hour

حاصلون على:



ISO 9001:2008



OHSAS 18001:2007



السلامة الأوروبية



التوحيد القياسي

المصانع

مدينة العاشر من رمضان

تليفون: ٠١٥/٣٦١٨٢٢ - ٠١٥/٣٦١٨٢٣ - فاكس: ٠١٥/٣٦٥٠٨٠

المخازن والمبيعات

١ شارع إدريس - الشرايية

تليفون: ٢٢٣٥٦٩١٧ - ٢٢٣٥٥٤١٦ - فاكس: ٢٢٣٣٨١٣٧



سلكوپلاست للكابلات (ش.م.م.)
SELCOPLAST CABLES CO. (S.A.E)

PRODUCT DATA SHEET

Over Sheath

Material Of Outer Jacket :

Thickness Of Outer Jacket :

Colour Of Outer Jacket :

Cable Dimension (Nominal) :

Nominal External Cable Diameter : 24.5 : 29.6 mm

Company : SELCOPLAST CABLES
Q.C. Department



ISO 9001:2008



OHSAS 18001:2007



السلامة الأوروبية



التوحيد القياسي

حاصلون على:

المصانع

مدينة العاشر من رمضان

تليفون: ٠١٥/٣٦١٨٢٢ - ٠١٥/٣٦١٨٢٣ - فاكس: ٠١٥/٣٦٥٠٨٠

المخازن والمبيعات

١ شارع إدريس - الشرايية

تليفون: ٢٢٣٥٦٩١٧ - ٢٢٣٥٥٤١٦ - فاكس: ٢٢٣٣٨١٣٧