سلكوبلاست للكابلات (ش.م.م.)
SELCOPLAST CABLES CO. (S.A.E)

PRODUCT DATA SHEET

Cable Description

Cable Size	**:**	*70 mm²*
Standard Specification Applied To Cable	**:**	*IEC 60502 - IEC 60228*
Rated Voltage	**:**	*600 / 1000 Volt*
Cable Description	**:**	*Stranded Copper Conductor Insulated With Polyvinyl Chloride And Sheathed With Polyvinyl Chloride(CU / PVC / PVC)*

Conductor

Standard Specification Applied To Conductor	**:**	*IEC 60228*
NO. Of Cores per Cable	**:**	*1*
Nominal Cross- Sectional Area Per core	**:**	*70 mm²*
Nominal Number Of Strands Per core	**:**	*19*
Diameter Of Each Strand	**:**	*2.15 mm*
Material Of Core	**:**	*Copper*
Type	**:**	*Class-2*
Cross- Sectional Area Of Each Strand	**:**	*3.628 mm²*
Overall Diameter Of Conductor	**:**	*10.75 mm*
D.C. Resistance Of Conductor At 20ċ Per Km (max.)	**:**	*0.268 Ω/km*

Insulation

Material Of Insulation	**:**	*Polyvinyl Chloride*
Colour Per Core	**:**	***……***
Nominal Thickness Of Insulation Per Core	**:**	*1.40 mm*
Min. Insulation Resistance Per Core Per Km Length Of Cable At 70ċ	**:**	*0.0035 M ohm.Km*
Test Voltage Between Cores And Earth (AC KV . Time min)	**:**	*3000V for 5 min*
Heat Resistance Test (Temperature ċ . Time min)	**:**	*150 ċ for 1 hour*

سلكوبلاست للكابلات (ش.م.م.)
SELCOPLAST CABLES CO. (S.A.E)

PRODUCT DATA SHEET

Over Sheath

Material Of Outer Jacket	:	*Polyvinyl Chloride*
Thickness Of Outer Jacket	:	*1.50 mm*
Colour Of Outer Jacket	:	.....

Cable Dimension (Nominal) :

Approx. External Cable Diameter	:	*16.55 mm*

Company : *SELCOPLAST CABLES*

Q.C. Depatment